

# SCJ Bitumenspray

Cold Seal and Tack Coat Spray



Sture Steens väg 2, SE-341 55 Vittaryd, Sweden  
Tel. +46 (0)370-472 00 · info@pekuma.se · www.pekuma.se

## Applications

SCJ is a bitumen cold joint sealer & tack coat spray that is applied onto vertical edges and the surface base before the application of asphalt. It will increase the bond of the material to the substrate and waterproof the area. This will significantly enhance the reinstatement's performance by preventing the ingress of water and freeze/thaw effect

## Technical

SCJ is supplied in 750ml spray cans, with the bitumen being discharged by inverting the container and pressing the spray button.

## Preparation

Remove as much standing water and loose particles as possible prior to product application. The sealer can be applied to damp or dry surfaces.

## Application

Hold the can tightly and shake vigorously before use. Invert the can and press the spray button. Cover the area to be sealed with long strokes from a distance of 175mm to 250mm, working from the top downwards. Ensure that the entire surface is covered.

## Cleaning

Point nozzle upward immediately after use and spray for a few seconds to clear it, taking care not to spray into wind. Failure to clean the nozzle after use could result in the aerosol becoming blocked rendering the product unusable.

## Storage

Aerosol cans must NOT be exposed to direct sunlight or temperatures above 50°C. Store in a cool well-ventilated place.

## Shelf life

Shelf life in correct conditions for sealed goods is 24 months.

## Health, Safety and Environmental

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash your hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste responsibly and in accordance with local authority requirements. A full material datasheet relating to this product is available from [pekuma.se](http://pekuma.se)



## Features and benefits

- HAPAS Approved since 2005
- Prevents water ingress
- Improves bond
- Prolongs the life of your repair
- Can be used in all weathers